# **Strobes**

By NookSchoenfeld

he days of xenon bulbs in strobes is just about over. Diversitronics, the one-time leader in the market, has stopped making fixtures, but they still sell bulbs. Solaris Strobe still offers one, and you may still be able to find a Lightning Strike in a Hollywood shop. The GAM Star Strobe (marketed by Rosco) is now a double-ended xenon flicker, but everyone else is now LED. The Martin Atomic got itself an Aura. The Ayrton MagicBurst is a strobe machine unlike any other. GLP may just be the leader these days with lots of functions — and a strobe with a tilt function. And all these babies are bright. Happy shopping, and be glad you're just looking a photos and not actual units fired up at 100 percent.

### Blizzard Lighting Cyc Out

**Light Source:** 64 RGBW 3W LEDs lumber of Individual Cells: 2 Input Voltage: 100-264V Output Wattage: 663W Beam Angle: 60° Flashes Per Second: 25 Control Protocols: DMX Max. # Control Channels: 9, 15, 27 **Does Fixture Thermal Out: No** Motorized Pan and Tilt: No Color Mixing: Yes Size: 10" x 17.8" x 6" Weight: 16.3 lbs. IP Rating: IP20

MSRP: Call for quote

More Info: Strobe offers 256 3W

LEDs, dual zone control via DMX.

RGBW intensity, strobe duration

and rate control, barn doors, 32-bit dimming, micro OLED display.



**Does Fixture Thermal Out:** Yes

More Info: Built-in macros like

burst, pulse and lightning.

**Size:** 10.25 x 18.9 x 5"

Weight: 17 lbs.

IP Rating: N/A

MSRP: \$1,119

Motorized Pan and Tilt: No

Color Mixing: Yes

Weight: 24.3 lbs.

IP Rating: IP20

MSRP: \$1,600

**Size:** 14.1 x 5.9 x 19.9"

### blizzardlighting.com

# Elation Protron 3K Color

Light Source: 240 CREE XLamp 3W RGRW I FDs Number of Individual Cells: 1 Input Voltage: AC 100-240V Output Wattage: 800W Beam Angle: 63° Flashes Per Second: NA Control Protocols: DMX

Max. # Control Channels: 8

### Mega-Lite XL LED Strobe RGB



**Light Source:** 1,260 RGB SMD Number of Individual Cells: 3 Input Voltage: 110-240V Output Wattage: 1,008W Beam Angle: 140° Flashes Per Second: 1-10 Control Protocols: DMX Max. # Control Channels: 26 **Does Fixture Thermal Out: Yes Motorized Pan and Tilt:** No

megasystemsinc.com

### ADJ Lightning COB Cannon

Light Source: 100W White COB Input Voltage: Multi-voltage

100-240V) Output Wattage: 120W Beam Angle: 33° Flashes Per Second: 1-10 Control Protocols: DMX Max. # Control Channels: 3 DMX **Does Fixture Thermal Out:** No otorized Pan and Tilt: No

Color Mixing: No **Size:** 12.75" x 11" x 8" Weight: 11 lbs. MSRP: \$349.99 More Info: Light Source: 100W

COB, cool white (8,000K) LED



### adj.com

### Chauvet Professional Strike 1

Light Source: 1 LED (WW) 230W, 8 LEDs (Amber) 2W mber of Individual Cells: 1 Input Voltage: 100-240V Output Wattage: 266W eam Angle: 30° Flashes Per Second: 25 Control Protocols: DMX. RDM Max. # Control Channels: 6 **Does Fixture Thermal Out:** No corized Pan and Tilt: No Color Mixing: No **Size:** 14.96 x 7.40 x 14.61 Neight: 18.8 lbs. IP Rating: IP65 MSRP: \$1,229

More Info: Strike 1 is an IP65 rated

strobe/ blinder powered by an

intense 230W warm white LED



### chauvetprofessional.com

### GLP JDC1



Light Source: 216 White LEDs, 1,320 RGB LEDs lumber of Individual Cells: 24 Input Voltage: 100-240V Output Wattage: 1200W Beam Angle: 185° Flashes Per Second: 25 Control Protocols: DMX and

Max. # Control Channels: 68 **Does Fixture Thermal Out: No Motorized Tilt:** Yes Color Mixing: Yes **Size:** 15.3 x 6.1 x 11.2" Weight: 26.5 lbs. IP Rating: None MSRP: \$6,249

### germanlightproducts.com

### Philips Showline SL Nitro 510C

**Motorized Pan and Tilt:** No

More Info: Separate white emit-

ters deliver a true white strobe

effect without compromising

Color Mixing: Yes

Size: 16 x 11 x 4"

Weight: 17.6 lbs.

IP Rating: IP20

**MSRP:** \$ 2,165

performance.



**Light Source:** 264 RGB or White SMD LEDs

mber of Individual Cells: 6 Input Voltage: 100-240V Output Wattage: 360W eam Angle: 120° Flashes Per Second: 30

More Info: Mega-Lite XL LED Strobe W offers 1260 RGB SMD LEDs and 140° LED angle. Has Control Protocols: DMX, RDM three segments of control, a single mounting yoke and comes Max. # Control Channels: 6 with two mirror reflectors. **Does Fixture Thermal Out:** No

### Ayrton MagicBurst

Light Source: 3,840 LED sources mber of Individual Cells: 64 Input Voltage: 110V-240V

**Output Wattage: 1400W** Beam Angle: 120° Flashes Per Second: 25 Control Protocols: DMX. RDM-compatible, Art-Net, sACN Max. # Control Channels: 203 **Does Fixture Thermal Out:** No Notorized Pan and Tilt: Yes Color Mixina: No Size: 18.5 x 25 x 12" Weight: 41 lbs. IP Rating: IP20

MSRP: \$10.232

LED strobe with continuous


rotation on pan and tilt.

More Info: High-power graphic

### ayrton.eu

### Claypaky Stormy/Stormy CC

Light Source: 144 7W Oslon Osram mber of Individual Cells: 1 Input Voltage: 100-240V **Output Wattage: 980W** Beam Angle: 130° Flashes Per Second: N/A Control Protocols: DMX, RDM Max. # Control Channels: 14



without the power draw.



### claypaky.it

### Martin Atomic 3000 LED



**Light Source:** 228 x Cree XLamp **Max. # Control Channels:** 14 Number of LEDs: Input Voltage: 100-240V Output Wattage: 655W Beam Angle: NA Flashes Per Second: 0.289 to

Control Protocols: DMX, RDM

**Does Fixture Thermal Out:** No **Motorized Pan and Tilt:** No Color Mixing: No **Size:** 9.7 x 16.8 x 9.5" **Weight:** 17.2 lbs. IP Rating: IP 20 MSRP: \$3,390

### PR Lighting Blinder 360

**Light Source:** 1260 RGB SMD LEDs mber of Individual Cells: 8 Input Voltage: 100-240V **Output Wattage: 360** Beam Angle: 120° Flashes Per Second: 25 Control Protocols: DMX Max. # Control Channels: 20 **Motorized Pan and Tilt:** Yes **Color Mixing: No Size:** 14 x 10 x 10" Weight: 12.5 lbs. IP Rating: IP20

with eight-segment control.

MSRP: \$1,399



megasystemsinc.com



**Light Source:** 120 White LED **Number of Individual Cells: 12** Input Voltage: 85-305V Output Wattage: 840W Beam Angle: 32° Flashes Per Second: 30 Control Protocols: DMX, RDM, Art-Net, MA-Net, sACN

Max. # Control Channels: 20 Does Fixture Thermal Out: No Motorized Pan and Tilt: No Color Mixing: No **Size:** 7.5 x 17. 7x 11.8" Weight: 24 lbs. IP Rating: IP22 MSRP: Call for quote

# Rosco GAM SS3115 StarStrobe Double

Light Source: 4 x 20W Xenon Input Voltage: 120 or 230V **Output Wattage: 74W** Beam Angle: 360° Flashes Per Second: Up to 1 Control Protocols: Via AC or DC

Max. # Control Channels: 1 **Does Fixture Thermal Out:** No otorized Pan and Tilt: No Color Mixing: No **Size:** 9.5 x 2.5" Weight: 7 oz. IP Rating: N/A

MSRP: \$249 More Info: Updated version of the Star Strobe w/strobe capsules at

### Light Source: 48 24W RGBW Number of Individual Cells: 8 Input Voltage: 100-240V Output Wattage: 1250W Beam Angle: 10° native (others Flashes Per Second: 50+ Control Protocols: DMX, RDM, Wireless CRMX, W-DMX Max. # Control Channels: 30 ch **Does Fixture Thermal Out:** No **Motorized Pan and Tilt:** No Color Mixing: Yes **Size:** 15.8 x 8.1 x 27.6" Weight: 43.65 lbs. IP Rating: IP65 MSRP: \$5,900



**Light Source:** Cree LED nber of Individual Cells: Input Voltage: 100-240V **Output Wattage: 840W** Beam Angle: 120° Flashes Per Second: 60 Control Protocols: DMX, RDM Max. # Control Channels: 4 **Does Fixture Thermal Out: No** 

Motorized Pan and Tilt: No Color Mixing: N Size: 14 2 x 3 75 x 3 15" Weight: 4.75 lbs. IP Rating: N/A MSRP: Call for quote More Info: Full RDM functionality, 2400Hz flicker-free modes. Optional floor/desk stand.

### Solaris Strobes Quasar 15K



Light Source: 15kW Xenon nber of Individual Cells: 1 Input Voltage: 208-240V Output Wattage: 15kW Beam Angle: 165° Flashes Per Second: 60 Control Protocols: DMX RDM Max. # Control Channels: 4 **Does Fixture Thermal Out:** Yes

**Motorized Pan and Tilt:** No Color Mixing: No Size: 75 x 215 x 55" Weight: 7.8 lbs. IP Rating: cETLus listed MSRP: Call for quote More Info: Full RDM functionality, optional barn door to cut down beam angle.

## Techni-Lux ST-LEDStrobe330

Light Source: 330 x .5W LFDs nber of Individual Cells: 10 Input Voltage: 90-250V Output Wattage: 150W Beam Angle: N/A Flashes Per Second: N/A Control Protocols: DMX Max. # Control Channels: 10 Does Fixture Thermal Out: Ye Motorized Pan and Tilt: No Color Mixing: No **Size:** 12.4 x 10.4 x 4.4" Weight: 14.3 lbs. IP Rating: IP20 **MSRP:** \$369 More Info: Double yoke works

as floor stand. 10 concentric rings of LEDS to chase.

# The Premier Haze Generator by Master FX **WE'VE GOT YOU COVERED** Every machine is backed by an industry leading 10 YEAR WARRANTY on all parts and service. MYSTIC 8000 **FLUID VARIETY** The Mystic offers two atmospheric effects fluids. Nebulous (thin density) and Obscure (thick density). **MAXIMIZED OUTPUT** The haze and fan output control from 0 -100% gives you ultimate command for any scale event **SELF CLEANING** The intuitive operating system automatically cleans the lines prior to shut down preventing residue build up.

\*Official Haze Generator of The Guinness World Record Largest Laser Show\* AVAILABLE EARLY 2018, PRE-ORDER NOW AT MASTERFX.COM | 877.578.6577



DECEMBER 2017 • plsn.com plsn.com • DECEMBER 2017 61